

Quotation: Ceiling/wall/post mount fan 36" single 115/230 or 3 phase 240/480 VAC, direct drive, barrel style with heavy duty/high efficiency motor.

The heavy-duty motor mount is connected directly to the multi-positional hanging bracket, meaning the poly housing is not part of the support structure so it will not distort like other poly fans.

- Available in 24" 1/2hp 5,000 cfm
- Fan ships completely assembled, 110/230V models with 10' cord/plug
- One-piece molded black polyethylene housing WILL NOT RUST
- Round housing shape is easy to clean with no corners for dirt build up
- Heavy duty, corrosion resistant, powder coated brackets, motor mount and guard, 1ph (6.2/3.1A) or 3 ph (2.6/1.3A), **10,120 CFM/1 ph, 9,770 CFM/3 ph**
- Multi-position mounting bracket lets you tilt and lock the fan in place
- Corrosion resistant, black powder coated guards meet OSHA requirements
- 3-blade galvanized or aluminum prop (24" fan)
- Totally enclosed, maintenance-free, direct drive high- efficiency motors have
- completely sealed ball bearings, are UL and CUL recognized, and are covered by a 2 year warranty.

Please allow 2-4 weeks shipping to location (estimated \$100/1 unit shipping). Can stack 4 fans on pallet.



Notes: Please specify single or 3 phase motors to be used while ordering.

Exclusions: Actual physical installation and electrical hook up is not included, bracket extra, wall/post mount or 4.5" column mount (\$70.00 per bracket).

Robert Drozdowski

Robert Drozdowski

rdrozdowski@agricontrol.com

Cell. 901-4174785

Fax. 901-339-0166

ACT/BTU SE USA Division in Memphis, TN